

39 688

RAPID SL

SLIM 2" X 4" IN-WALL CARRIER AND TANK FOR TOILET

Pure Freude
an Wasser



STANDARD SPECIFICATION:

- Slim tank fits standard 2" x 4" stud walls
- Dual flush – 0.8gpf and 1.6gpf (3L and 6L)
- Low noise operation – meets strict European noise (DIN) standards
- No tools required for the installation of the inspection shaft including protection during construction phase, for vertical use
- Self-supporting, pre-assembled powder coated steel frame with quick and lockable adjustments
- ADA Compliant, bowl rim height adjustment from 15" to 19"
- Pneumatic discharge valve offering 3 modes of operation: dual flush, start/stop or single flush
- Tank insulated to prevent condensation
- 2 fixing bolts included, 7- 9in (180-230mm) mounting screw distance
- 1/2" water supply connection from top, integrated angle valve
- Actuation plate sold separately
- TÜV approved for load capacity
- 44" (1.13m) installation height
- CALGreen compliant
- WaterSense® compliant when paired with listed WaterSense® high efficiency compatible 0.8-1.28gpf (3-4.8lpf) wall hung toilet bowls
- For use with small flush plates 5 1/8" x 6 3/4" (130 x 172 mm), please order shaft 40 911 000 (sold separately)

PRODUCT FEATURES:

 GROHE Whisper®

 GROHE EcoJoy™

 GROHE QuickFix®

CERTIFICATIONS:



- ADA
- Massachusetts Plumbing Board Approved
- ASSE 1002
- CSA B45.15
- CSA B125.12
- ASME A112.6.2
- ASME A112.19.5
- ASME A112.1002

AVAILABLE FINISHES:

39688000



NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

We reserve the right to make revisions without notice to product specifications. 12-01-2021

US
Tel: 1.630.582.7711 Fax: 1.630.582.7722
For the most current Specification Sheet,
go to www.grohe.us.

Canada
Tel: 1.888.644.7643 Fax: 1.905.366.2071
For the most current Specification Sheet,
go to www.grohe.ca.

PART OF **LIXIL**

39 688

RAPID SL

SLIM 2" X 4" IN-WALL CARRIER AND TANK FOR TOILET

Pure Freude
an Wasser



TECHNICAL DATA:

