

INSTALLATION INSTRUCTIONS


K1-3600

CROSS HANDLE 4-HOLE KITCHEN MIXER WITH PULL-OUT HAND SPRAY


K1-3601

LEVER 4-HOLE KITCHEN MIXER WITH PULL-OUT HAND SPRAY

K1-3600




K1-3601




LEFROY BROOKS

Dimensions in Inches (& Millimetres)

K1-3600



K1-3601




Whilst every effort is made to ensure accuracy, design and dimensions are subject to change without notice as part of the company's product development process.

What you need to know

Tools:

Adjustable Wrench
Groove Joint Pliers
Hacksaw
Phillips Screwdriver
Pipe Tape
Spatula
Spirit Level



Safety Tips

If you are soldering during faucet installation, remove cartridges, seats, gaskets and washers prior to applying flame, otherwise you will void the warranty.

Cover drain openings to avoid losing small parts.

When cutting or soldering pipe, use safety glasses to protect your eyes.

Things You May Need

Correct installation may vary depending on previous faucet installation. All necessary supplies required for faucet installation are not included, but may be found where plumbing supplies are sold. It is suggested that IAPMO and/or CSA approved plumbing supplies are used during installation.

Standards

IAPMO/cUPC Listed
Meets NSF 61-9
Meets A112.18.1

Maintenance

Your new bathroom faucet is designed for years of trouble-free performance.

Keep it looking new by cleaning it periodically with a soft cloth. Avoid abrasive cleaners, wire wool and harsh chemicals as these will dull the finish and void your warranty.


Important Points

Prior to beginning installation, turn off the cold and hot water lines and open the old faucet to release built-up pressure.

Overtightening nuts may cause damage.

Wrap all threaded connections with pipe tape available at your local plumbing supply store. Always wrap in a clockwise direction. The fittings should be installed by a state-licensed plumber.

Flow Rate




Please note :

Final achievable flow rate is dependent on the outlets fitted, see relevant outlets (spouts, roses, sprays) for fully assembled product flow rate.

Steps 1-5

Installation Procedure

Lefroy Brooks always recommends that plumbing products be installed by a licensed professional. Shut off main water supply before installation.



1 Position the spout in the second hole of sink. Insert spout into the mounting hole in deck from above. From underneath the sink, install the washers and lock nut. Slide on adapter over bottom of spout shank, and tighten with lock nut.

2 Place the handle body through side hole. Re-assemble the mounting hardware onto valve shank; use phillips screwdriver for final tightening.

3 Fix the handle with set screw provided.


4 Install the other handle assembly and body.

5 Connect flexible hoses. Alternative nuts are supplied in case you want to connect copper pipes instead.

Steps 6-8

Installation Procedure

Lefroy Brooks always recommends that plumbing products be installed by a licensed professional. Shut off main water supply before installation.



6 Install spray holder in sink deck: insert the spray holder from above into the mounting hole. Tighten with lock nut.

7 Insert spray hose through spray holder and install the hose adaptor to the shank. Screw side spray onto spray hose.

8 After installing faucet, remove aerator and open the hot and cold water supplies. Check for leaks. Turn on faucet handles for one minute to flush debris from faucet. Close the handles and re-assemble the aerator.


Warning! When installing flexible hose, please notice:

1. There should be no torsion or deformation
2. Do not fold into a V or L shape.
3. Do not use if there is any crack or deformation.

Exploded View

Parts List


K1-3600



1	Handle (H) (069688H)	16	Oil-seal (010095N)	31	Washer (013018)
2	Set screw (053205)	17	Aerator assembly (553648N)	32	Nut (009012)
3	Stem extension (205417)	18	O-ring (063072N)	33	Screw (008045)
4	Screw (008774)	19	O-ring (004074N)	34	Screw (053197)
5	Screw (065152)	20	Canopy (000888)	35	Handle (C) (069688C)
6	Adaptor (205434)	21	Clip (012101)	36	Side spray (503125W)
7	Canopy (018419)	22	Clip (012195N)	37	Holster (017005)
8	Cartridge (507907N)	23	Escutcheon (303427)	38	Escutcheon (220640)
9	Escutcheon (071308)	24	Diverter (501013N)	39	Spray hose (511422W)
10	O-ring (004072N)	25	Diverter seat (213129W)	40	Spring (005195)
11	Oil-seal (010017)	26	Flexible hose (105750N)	41	Nut (009008)
12	Washer (013158)	27	O-ring (004026N)	42	Body (066121W)
13	Nut (009834)	28	Conneting tube (035231N)	43	O-ring (063091N)
14	Body (061893W)	29	Allen key (031003)	44	Connector (014083W)
15	Spout assembly (139836W-54)	30	Alternative nut (504003)	45	Nut (070053)

Parts List

K1-3601




1	Spout assembly (139836W-54)	17	Allen key (031003)	33	Screw (053197)
2	Handle (H) (069699H)	18	Alternative nut (504003)	34	Handle (C) (069699C)
3	Set screw (053205)	19	Oil-seal (010095N)	35	Side spray (503125W)
4	Stem extension (205417)	20	O-ring (063072N)	36	Holster (017005)
5	Screw (008774)	21	Aerator assembly (553648N)	37	Spray hose (511422W)
6	Screw (065152)	22	O-ring (004074N)	38	Escutcheon (220640)
7	Adaptor (205434)	23	Canopy (000888)	39	Cartridge (C) (507176N)
8	Canopy (018419)	24	Clip (012101)	40	Nut (009008)
9	Cartridge (H) (507175N)	25	Clip (012195N)	41	Spring (005195)
10	Escutcheon (071308)	26	Escutcheon (303427)	42	Screw (008045)
11	O-ring (004072N)	27	Diverter (501013N)	43	Body (066121W)
12	Oil-seal (010017)	28	Diverter seat (213129W)	44	O-ring (063091N)
13	Washer (013158)	29	O-ring (004026N)	45	Connector (014083W)
14	Nut (009834)	30	Connecting tube (035231N)	46	Nut (070053)
15	Body (061893W)	31	Washer (013018)		
16	Flexible hose (105750N)	32	Nut (009012)		

For additional assistance or service call

718-302-5292

9am to 5pm EST Monday to Friday



L E F R O Y B R O O K S

www.lefroybrooks.com

LEFROY BROOKS INC, 1828 TROUTMAN STREET, RIDGEWOOD, NY, 11385
TELEPHONE: 718-302-5292. FAX: 718-302-4177

The use of trademarks, product design and artwork is subject to licence or agreement with LBIP Ltd. The design registrations, trademark registrations and copyrights are protected by law and the use or reproduction outside the terms of an agreement is prohibited. The right to modify designs and dimensions is reserved. Christo Lefroy Brooks is a member of ACID (Anti Copying in Design).